

PRODUCTS AND PRICES OF *XINJE Electronic*

XD series PLC

1. XD3 series PLC

Model	Functions	Price (EUR)
XD3-16R-E	8 input/8 output, relay output, power supply AC100~240V, 2 AB phases counter, it has faster processing speed than XC series PLC, DC24V output rated current 200mA.	91,00
XD3-16T-E	8 input/8 output, transistor output, power supply AC100~240V, 2 AB phases counter, 2 high speed pulse, it has faster processing speed than XC series PLC, DC24V output rated current 200mA.	91,00
XD3-16RT-E	8 input/8 output, transistor and relay output, power supply AC100~240V, 2 AB phases counter, 2 high speed pulse, it has faster processing speed than XC series PLC, with clock, DC24V output rated current 200mA.	91,00
XD3-16R-C	8 input/8 output, relay output, power supply DC24V, 2 AB phases counter, it has faster processing speed than XC series PLC, DC24V output rated current 200mA.	91,00
XD3-16T-C	8 input/8 output, transistor output, power supply DC24V, 2 AB phases counter, 2 high speed pulse, it has faster processing speed than XC series PLC, DC24V output rated current 200mA.	91,00
XD3-16RT-C	8 input/8 output, transistor and relay output, power supply DC24V, 2 AB phases counter, 2 high speed pulse, it has faster processing speed than XC series PLC, with clock, DC24V output rated current 200mA.	91,00
XD3-24R-E	14 input/10 output, relay output, power supply AC100~240V, 3 AB phases high speed counter, it has faster processing speed than XC series PLC, DC24V output rated current 400mA.	119,00
XD3-24T-E	14 input/10 output, transistor output, power supply AC100~240V, 3 AB phases counter, 2 high speed pulse, it has faster processing speed than XC series PLC, DC24V output rated current 400mA.	119,00

XD3-24RT-E	14 input/10 output, relay and transistor output, power supply AC100~240V, 3 AB phases high speed counter, 2 high speed pulse, it has faster processing speed than XC series PLC, DC24V output rated current 400mA.	119,00
XD3-24R-C	14 input/10 output, relay output, power supply DC24V, 3 AB phases high speed counter, it has faster processing speed than XC series PLC, DC24V output rated current 400mA.	119,00
XD3-24T-C	14 input/10 output, transistor output, power supply DC24V, 3 AB phases counter, 2 high speed pulse, it has faster processing speed than XC series PLC, DC24V output rated current 400mA.	119,00
XD3-24RT-C	14 input/10 output, relay and transistor output, power supply DC24V, 3 AB phases high speed counter, 2 high speed pulse, it has faster processing speed than XC series PLC, DC24V output rated current 400mA.	119,00
XD3-32R-E	18 input/14 output, relay output, power supply AC100~240V, 3 AB phases counter, it has faster processing speed than XC series PLC, DC24V output rated current 400mA	139,00
XD3-32T-E	18 input/14 output, transistor output, power supply AC100~240V, 3 AB phases counter, 2 high speed pulse, it has faster processing speed than XC series PLC, DC24V output rated current 400mA	139,00
XD3-32RT-E	18 input/14 output, relay and transistor output, power supply AC100~240V, 3 AB phases counter, it has faster processing speed than XC series PLC, DC24V output rated current 400mA	139,00
XD3-32R-C	18 input/14 output, relay output, power supply DC24V, 3 AB phases counter, it has faster processing speed than XC series PLC, DC24V output rated current 400mA	139,00
XD3-32T-C	18 input/14 output, transistor output, power supply DC24V, 3 AB phases counter, it has faster processing speed than XC series PLC, DC24V output rated current 400mA	139,00
XD3-32RT-C	18 input/14 output, relay and transistor output, power supply DC24V, 3 AB phases counter, 2 high speed pulse, it has faster processing speed than XC series PLC, DC24V output rated current 400mA	139,00
XD3-48R-E	28 input/20 output, relay output, power supply AC100~240V, 3 AB phases counter, it has faster processing speed than XC series PLC, DC24V output rated current 400mA	174,00
XD3-48T-E	28 input/20 output, transistor output, power supply AC100~240V, 3 AB phases counter, 2 high speed pulse, it has faster processing speed than XC series PLC, DC24V output rated current 400mA	174,00
XD3-48RT-E	28 input/20 output, relay and transistor output, power supply AC100~240V, 3 AB phases counter, 2 high speed pulse, it has faster processing speed than XC series PLC, DC24V output rated current 400mA	174,00
XD3-48R-C	28 input/20 output, relay output, power supply DC24V, 3 AB phases counter, it has faster processing speed than XC series PLC, DC24V output rated current 400mA	174,00
XD3-48T-C	28 input/20 output, transistor output, power supply DC24V, 3 AB phases counter, 2 high speed pulse, it has faster processing speed than XC series PLC, DC24V output rated current 400mA	174,00

XD3-48RT-C	28 input/20 output, relay and transistor output, power supply DC24V, 3 AB phases counter, 2 high speed pulse, it has faster processing speed than XC series PLC, DC24V output rated current 400mA	174,00
XD3-60R-E	36 input/24 output, relay output, power supply AC100~240V, 3 AB phases counter, it has faster processing speed than XC series PLC, DC24V output rated current 400mA	217,00
XD3-60T-E	36 input/24 output, transistor output, power supply AC100~240V, 3 AB phases counter, 2 high speed pulse, it has faster processing speed than XC series PLC, DC24V output rated current 400mA	217,00
XD3-60RT-E	36 input/24 output, relay and transistor output, power supply AC100~240V, 3 AB phases counter, 2 high speed pulse, it has faster processing speed than XC series PLC, DC24V output rated current 400mA	217,00
XD3-60R-C	36 input/24 output, relay output, power supply DC24V, 3 AB phases counter, it has faster processing speed than XC series PLC, DC24V output rated current 400mA	217,00
XD3-60T-C	36 input/24 output, transistor output, power supply DC24V, 3 AB phases counter, 2 high speed pulse, it has faster processing speed than XC series PLC, DC24V output rated current 400mA	217,00
XD3-60RT-C	36 input/24 output, relay and transistor output, power supply DC24V, 3 AB phases counter, 2 high speed pulse, it has faster processing speed than XC series PLC, DC24V output rated current 400mA	217,00

NOTE:

1. All XD3-PLC are equipped with RTC; can expand BD card and expansions;
2. All XD3 support free format communication.
3. Except XD3-16, XD3-PLC can expand up to 2 BD cards, 1 ED module (left expansion) and 10 right expansions
4. XD3-16 can expand only one ED module (left module)
5. 2 channels 200KHz high speed pulse output

2. XD5 series PLC

Model	Functions	Price (EUR)	
XD5-16R-E	8 input/8 output, relay output, power supply AC100~240V, 3 AB phases high speed counter, DC24V output rated current 200mA.	109,00	No BD
XD5-16R-C	8 input/8 output, relay output, power supply DC24V, 3 AB phases high speed counter, DC24V output rated current 200mA.	109,00	expans

XD5-16T-E	8 input/8 output, transistor output, power supply AC100~240V,3 AB phases high speed counter, 2 high speed pulse, DC24V output rated current 200mA.	109,00	
XD5-16T-C	8 input/8 output, transistor output, power supply DC24V,3 AB phases high speed counter, 2 high speed pulse, DC24V output rated current 200mA.	109,00	
XD5-16RT-E	8 input/8 output, transistor and relay output, power supply AC100~240V,3 AB phases high speed counter, 2 high speed pulse, DC24V output rated current 200mA.	109,00	
XD5-16RT-C	8 input/8 output, transistor and relay output, power supply DC24V, 3 AB phases high speed counter, 2 high speed pulse, DC24V output rated current 200mA.	109,00	
XD5-24R-E	14 input/10 output, relay output, power supply AC100~240V, 3 AB phases high speed counter, DC24V output rated current 400mA.	126,00	
XD5-24T-E	14 input/10 output, transistor output, power supply AC100~240V, 3 AB phases counter, 2 high speed pulse,DC24V output rated current400mA.	126,00	
XD5-24RT-E	14 input/10 output, relay and transistor output, power supply AC100~240V, 3 AB phases high speed counter, 2 high speed pulse, DC24V output rated current 400mA.	126,00	
XD5-24R-C	14 input/10 output, relay output, power supply DC24V, 3 AB phases high speed counter, DC24V output rated current 400mA.	126,00	
XD5-24T-C	14 input/10 output, transistor output, power supply DC24V, 3 AB phases counter, 2 high speed pulse,DC24V output rated current400mA.	126,00	
XD5-24RT-C	14 input/10 output, relay and transistor output, power supply DC24V, 3 AB phases high speed counter, 2 high speed pulse, DC24V output rated current 400mA.	126,00	1 BD c expans
XD5-32R-E	18 input/14 output, relay output, power supply AC100~240V, 3 AB phases counter,DC24V output rated current 400mA	151,00	
XD5-32T-E	18 input/14 output, transistor output, power supply AC100~240V, 3 AB phases counter, 2 high speed pulse, DC24V output rated current 400mA	151,00	
XD5-32RT-E	18 input/14 output, relay and transistor output, power supply AC100~240V, 3 AB phases counter,DC24V output rated current 400mA	151,00	
XD5-32R-C	18 input/14 output, relay output, power supply DC24V, 3 AB phases counter,DC24V output rated current 400mA	151,00	
XD5-32T-C	18 input/14 output, transistor output, power supply DC24V, 3 AB phases counter,DC24V output rated current 400mA	151,00	

XD5-32RT-C	18 input/14 output, relay and transistor output, power supply DC24V, 3 AB phases counter, 2 high speed pulse, DC24V output rated current 400mA	151,00	
XD5-48R-E	28 input/20 output, relay output, power supply AC100~240V, 3 AB phases counter, DC24V output rated current 400mA	189,00	
XD5-48T-E	28 input/20 output, transistor output, power supply AC100~240V, 3 AB phases counter, 2 high speed pulse, DC24V output rated current 400mA	189,00	
XD5-48RT-E	28 input/20 output, relay and transistor output, power supply AC100~240V, 3 AB phases counter, 2 high speed pulse, DC24V output rated current 400mA	189,00	
XD5-48R-C	28 input/20 output, relay output, power supply DC24V, 3 AB phases counter, DC24V output rated current 400mA	189,00	
XD5-48T-C	28 input/20 output, transistor output, power supply DC24V, 3 AB phases counter, 2 high speed pulse, DC24V output rated current 400mA	189,00	
XD5-48RT-C	28 input/20 output, relay and transistor output, power supply DC24V, 3 AB phases counter, 2 high speed pulse, DC24V output rated current 400mA	189,00	2 BD c expans
XD5-60R-E	36 input/24 output, relay output, power supply AC100~240V, 3 AB phases counter, DC24V output rated current 400mA	234,00	
XD5-60T-E	36 input/24 output, transistor output, power supply AC100~240V, 3 AB phases counter, 2 high speed pulse, DC24V output rated current 400mA	234,00	
XD5-60RT-E	36 input/24 output, relay and transistor output, power supply AC100~240V, 3 AB phases counter, 2 high speed pulse, DC24V output rated current 400mA	234,00	
XD5-60R-C	36 input/24 output, relay output, power supply DC24V, 3 AB phases counter, DC24V output rated current 400mA	234,00	
XD5-60T-C	36 input/24 output, transistor output, power supply DC24V, 3 AB phases counter, 2 high speed pulse, DC24V output rated current 400mA	234,00	
XD5-60RT-C	36 input/24 output, relay and transistor output, power supply DC24V, 3 AB phases counter, 2 high speed pulse, DC24V output rated current 400mA	234,00	
XD5-24T4-E	14input/10output, ,transistor output, power supply AC100~240V, 4 AB phases counter, 4 high speed pulse, PID function, USB, RS232, RS485 port.	159,00	1 BD c expans
XD5-24T4-C	14input/10output, ,transistor output, power supply DC24V, 4 AB phases counter, 4 high speed pulse, PID function, USB, RS232, RS485 port.	159,00	

XD5-32T4-E	18input/14output, ,transistor output, power supply AC100~240V, 4 AB phases counter, 4 high speed pulse, PID function, USB, RS232, RS485 port.	177,00	
XD5-32T4-C	18input/14output, ,transistor output, power supply DC24V, 4 AB phases counter, 4 high speed pulse, PID function, USB, RS232, RS485 port.	177,00	
XD5-48T6-E	28 input/20 output, transistor output, power supply AC100~240V, 6 AB phases counter, 6 high speed pulse, PID function, USB, RS232, RS485 port.	205,00	
XD5-48T6-C	28 input/20 output, transistor output, power supply DC24V, 6 AB phases counter, 6 high speed pulse, PID function, USB, RS232, RS485 port.	205,00	2 BD c expans
XD5-60T6-E	36 input/24 output, transistor output, power supply AC100~240V, 6 AB phases counter, 6 high speed pulse, PID function, USB, RS232, RS485 port.	257,00	
XD5-60T6-C	36 input/24 output, transistor output, power supply DC24V, 6 AB phases counter, 6 high speed pulse, PID function, USB, RS232, RS485 port.	257,00	
XD5E-24R-E	14 input/10 output, relay output, power supply AC100~240V, 3 AB phases high speed counter, support Ethernet	162,00	
XD5E-24T-E	14 input/10 output, transistor output, power supply AC100~240V, 3 AB phases counter, 2 high speed pulse, support Ethernet	162,00	
XD5E-30R-E	16 input/14 output, relay output, power supply AC100~240V, 3 AB phases counter, support Ethernet	211,00	1 BD c expans
XD5E-30T-E	16 input/14 output, transistor output, power supply AC100~240V, 3 AB phases counter, 2 high speed pulse, support Ethernet	211,00	
XD5E-30T4-E	16input/14output, ,transistor output, power supply AC100~240V, 4 AB phases counter, 4 high speed pulse, PID function, USB, RS232, RS485 port, support Ethernet	234,00	
XD5E-30T4-C	16input/14output, ,transistor output, power supply DC24V, 4 AB phases counter, 4 high speed pulse, PID function, USB, RS232, RS485 port, support Ethernet	234,00	
XD5E-48T-E	28 input/20 output, transistor output, power supply AC100~240V, 3 AB phases counter, 2 high speed pulse, support Ethernet	240,00	
XD5E-60T-E	36 input/24 output, transistor output, power supply AC100~240V, 3 AB phases counter, 2 high speed pulse, support Ethernet	299,00	2 BD c expans
XD5E-60T6-E	36 input/24 output, transistor output, power supply AC100~240V, 6 AB phases counter, 6 high speed pulse, PID function, USB, RS232, RS485 port, support Ethernet	337,00	
XD5E-60T6-C	36 input/24 output, transistor output, power supply DC24V, 6 AB phases counter, 6 high speed pulse, PID function, USB, RS232,RS485 port, support Ethernet	337,00	

XD5E-60T10-E	36 input/24 output, transistor output, power supply AC100~240V, 10 AB phases counter, 10 high speed pulse, PID function, USB, RS232, RS485 port, support Ethernet	362,00
XD5E-60T10-C	36 input/24 output, transistor output, power supply DC24V, 10 AB phases counter, 10 high speed pulse, PID function, USB, RS232, RS485 port, support Ethernet	362,00

NOTE:

1. XD5-PLC can expand up to 2 BD cards, 1 left expansion (ED module) and 16 right expansions
2. XD5-PLC support free format communication

3. XDM series PLC (motion control type)

Model	Functions	Price (EUR)	
XDM-24T4-E	14 input/10 output, transistor output, power supply AC100~240V, 4 AB phases counter, 4 high speed pulse(Two axis line, circular interpolation),with PID operation, electronic cam, USB and 485 port, it has tracking control function, it can also be extended by BD board and modules.	205,00	1 BD c expans
XDM-24T4-C	14 input/10 output, transistor output, power supply DC24V, 4 AB phases counter, 4 high speed pulse(Two axis line, circular interpolation),with PID operation, electronic cam, USB and 485 port, it has tracking control function, it can also be extended by BD board and modules.	205,00	
XDM-32T4-E	18 input/14 output, transistor output, power supply AC100~240V, 4 AB phases counter, 4 high speed pulse(Two axis line, circular interpolation),with PID operation, electronic cam, USB and 485 port, it has tracking control function, it can also be extended by BD board and modules.	245,00	2 BD c expans
XDM-32T4-C	18 input/14 output, transistor output, power supply DC2.4V, 4 AB phases counter, 4 high speed pulse(Two axis line, circular interpolation),with PID operation, electronic cam, USB and 485 port, it has tracking control function, it can also be extended by BD board and modules.	245,00	
XDM-60T4-E	36 input/24 output, transistor output, power supply AC100~240V, 4 AB phases high speed counter, 4 high speed pulse(Two axis line, circular interpolation),with PID operation ,electronic cam, USB and 485 port, it has tracking control function, it can also be extended by BD board and modules.	359,00	2 BD c expans
XDM-60T4-C	36 input/24 output, transistor output, power supply DC24V, 4 AB phases high speed counter, 4 high speed pulse(Two axis line, circular interpolation),with PID operation ,electronic cam, USB and 485 port, it has tracking control function, it can also be extended by BD board and modules.	359,00	

XDM-60T10-E	36 input/24 output, transistor output, power supply AC100~240V, 10 AB phases high speed counter, 10 high speed pulse(Two axis line, circular interpolation),with PID operation, electronic cam, USB and 485 port, it has tracking control function, it can also be extended by BD board and modules.	419,00
XDM-60T10-C	36 input/24 output, transistor output, power supply DC24V,1 0 AB phases high speed counter, 10 high speed pulse(Two axis line, circular interpolation),with PID operation, electronic cam, USB and 485 port ,it has tracking control function, it can also be extended by BD board and modules.	419,00

NOTE:

1. XDM series PLC can expand 2pcs BD cards and 16pcs modules.
2. XDM series PLC support free format communication.

4. XDH series		
XDH-60T4-C	36 input/24 output, transistor output, DC24V, 4 AB phases high speed counter, 4 high speed pulse(Two axis linear,circular interpolation), 2 Rj45 ports for Ethernet and EtherCAT , max. 32 axis via EtherCAT.	566,00
XDH-60T4-E	36 input/24 output, transistor output, AC100V~240V, 4 AB phases high speed counter, 4 high speed pulse(Two axis linear,circular interpolation), 2 Rj45 ports for Ethernet and EtherCAT , max. 32 axis via EtherCAT.	566,00

5. XDH motion control series

Model	Functions	Price (EUR)
XDH-30A16-E	16 input/14 output, transistor output, AC100V~240V, 4 AB phases high speed counter, 4 high speed pulse(Two axis linear,circular interpolation), 2 Rj45 ports for Ethernet and EtherCAT , max. 16 axis via EtherCAT, support single and multi axis motion control and electric CAM	543,00
XDH-30A16L-E	16 input/14 output, transistor output, AC100V~240V, 4 AB phases high speed counter, 4 high speed pulse(Two axis linear,circular interpolation), 2 Rj45 ports for Ethernet and EtherCAT , max. 16 axis via EtherCAT, support single and multi axis motion control and doesn't support electric CAM	368,00
XDH-30A16L-C	16 input/14 output, transistor output, DC 24V, 4 AB phases high speed counter, 4 high speed pulse(Two axis linear,circular interpolation), 2 Rj45 ports for Ethernet and EtherCAT , max. 16 axis via EtherCAT, support single and multi axis motion control and doesn't support electric CAM	368,00

XDH-60A32-E	36 input/24 output, transistor output, AC100V-240V, 4 AB phases high speed counter, 4 high speed pulse(Two axis linear,circular interpolation), 2 Rj45 ports for Ethernet and EtherCAT , max. 32 axis via EtherCAT, support single and multi axis motion control and electric CAM	686,00
XDH-60A64-E	36 input/24 output, transistor output, AC100V-240V, 4 AB phases high speed counter, 4 high speed pulse(Two axis linear,circular interpolation), 2 Rj45 ports for Ethernet and EtherCAT , max. 64 axis via EtherCAT, support single and multi axis motion control and electric CAM	768,00

6. Codesys Series PLC

XSDH-60A32-E	CPU 36 in/24 out, transistor output, AC220V power supply, 4 high-speed counting (one-way/AB-direction), 1 RS232, 1 RS485, two network ports (LAN1 is used for Ethernet communication, LAN2 supports Ethercat bus communication , CODESYS development platform , the programming environment fully conforms to the IEC-61131-3 standard) 16 modules can be expanded, support Ethercat bus and Ethernet communication , with axis capacity: 4 axis/1ms, 16 axis/2ms, 32 axis/4ms;	686,00
---------------------	---	---------------

7. XDC series PLC (motion control over X-NET)

Model	Functions	Price (EUR)	
XDC-24T-E	Special motion control X-NET Bus PLC, 14 input/10 output, transistor output, AC100V~240V, 4 AB phases high speed counter, 2 high speed pulse(Two axis linear, circular interpolation), PID operation, RS485 port, can expand BD cardsand ED module.	123,00	1 BD card, 1 ED module (Left expansion), 16 right expansion modules
XDC-24T-C	Special motion control X-NET Bus PLC, 14 input/10 output, transistor output, DC24V power supply, 4 AB phases high speed counter, 2 high speed pulse(Two axis linear, circular interpolation), PID operation, RS485 port, can expand BD cardsand ED module.	123,00	
XDC-32T-E	Special motion control X-NET Bus PLC, 18 input/14 output, transistor output, AC100V~240V, 4 AB phases high speed counter, 2 high speed pulse(Two axis linear, circular interpolation), PID operation, RS485 port, can expand BD cardsand ED module.	146,00	
XDC-32T-C	Special motion control X-NET Bus PLC, 18 input/14 output, transistor output, DC24V power supply, 4 AB phases high speed counter, 2 high speed pulse(Two axis linear, circular interpolation), PID operation, RS485 port, can expand BD cardsand ED module.	146,00	

XDC-48T-E	Special motion control X-NET Bus PLC, 28 input/20 output, transistor output, AC100V~240V, 4 AB phases high speed counter, 2 high speed pulse(Two axis linear, circular interpolation), PID operation, RS485 port, can expand BD cardsand ED module.	182,00	2 BD cards, 1 ED module (Left expansion), 16 right expansion modules
XDC-48T-C	Special motion control X-NET Bus PLC, 28 input/20 output, transistor output, DC24V power supply, 4 AB phases high speed counter, 2 high speed pulse(Two axis linear, circular interpolation), PID operation, RS485 port, can expand BD cardsand ED module.	182,00	
XDC-60T-E	Special motion control X-NET Bus PLC, 36 input/24 output, transistor output, AC100V~240V, 4 AB phases high speed counter, 2 high speed pulse(Two axis linear, circular interpolation), PID operation, RS485 port, can expand BD cardsand ED module.	228,00	
XDC-60T-C	Special motion control X-NET Bus PLC, 36 input/24 output, transistor output, DC24V power supply, 4 AB phases high speed counter, 2 high speed pulse(Two axis linear, circular interpolation), PID operation, RS485 port, can expand BD cardsand ED module.	228,00	
XDC-60C4-E	Special motion control X-NET Bus PLC, 36 input/24 output, transistor output, AC100V~240V, 4 AB phases high speed counter, 4 high speed pulse(4 axis interpolation), PID operation, electronic CAM, RS485 port, tracking control function; can expand BD and module.	237,00	
XDC-60C6-E	Special motion control X-NET Bus PLC, 36 input/24 output, transistor output, AC100V~240V, 4 AB phases high speed counter, 4 high speed pulse(6 axis interpolation), PID operation, electronic CAM, RS485 port, tracking control function; can expand BD and module.	248,00	

NOTE:

1. XDC-24, XDC-32 can expand 1 BD card, 1 ED module and 16 expansions; XDC-48, XDC-60 can expand 2 BD cards, 1 ED module and 16 expansions
2. XDC-PLC support free format communication
3. XDC-PLC supports motion control bus X-NET;

1. XD series I/O expansion modules

Model	Functions	Price (EUR)
XD-E8X	It can extend 8 DC input(NPN),positive and negative logic can be set, input filtering time is adjustable, 24VDC Power supply	46,00

XD-E16X	16 DC input, positive and negative logic can be set, input filtering time is adjustable. 24VDC Power supply	55,00
XD-E32X-E	Extend 32 DC input (NPN), positive and negative logic can be set, input filtering time is adjustable. AC100~240V	111,00
XD-E32X-C	Extend 32 DC input (NPN), positive and negative logic can be set, input filtering time is adjustable. DC24V	111,00
XD-E8X8YR	8 DC input/8 relay output, positive and negative logic can be set, input filtering time is adjustable. 24VDC Power supply	60,00
XD-E8X8YT	8 DC input/8 transistor output, positive and negative logic can be set, input filtering time is adjustable. 24VDC Power supply	60,00
XD-E16X16YR-E	16 DC input, 16 relay output, AC100~240V power supply	114,00
XD-E16X16YT-E	16 DC input, 16 transistor output, AC100~240V power supply	114,00
XD-E16X16YR-C	Extend 16 DC input, 16 relay output, DC24V power supply	114,00
XD-E16X16YT-C	Extend 16 DC input, 16 transistor output, DC24V power supply	114,00
Digital Output Expansion:		
XD-E8YR	Extend 8 relay output	54,00
XD-E8YT	Extend 8 transistor output	57,00
XD-E16YT	16 transistor output.	60,00
XD-E16YR	16 relay output.	60,00
XD-E32YR-E	Extend 32 relay output, AC100~240V power supply	117,00
XD-E32YR-C	Extend 32 relay output, DC24V power supply	117,00
XD-E32YT-E	Extend 32 transistor output, AC100~240V power supply	117,00
XD-E32YT-C	Extend 32 transistor output, DC24V power supply	117,00

2.XD-PLC Analog Expansion Modules

Model	Functions	Price (EUR)
XD-E4AD	14bit, 4 channel analog input (current or voltage), The first-stage coefficient is adjustable, Each channel can be individually enabled.	119,00
XD-E2DA	12bit, 2 channel analog output module(current or voltage)	134,00
XD-E4DA	12bit, 4 channel analog output module(current or voltage)	134,00
XD-E4AD2DA	14bit, 4 channel analog input (current or voltage), 12bit, 2 channel analog output module (voltage output is-10V~+10V), AD/DA All hardware isolation alone.	163,00
XD-E8AD	14bit, 8 channel analog input module, first 4 channels are voltage input, last 4 channels are current input, The first-order coefficient is adjustable, each channel can be individually enabled.	134,00
XD-E8AD-A	14bit, 8 channel analog input module, 8 channels are current input, The first-order coefficient is adjustable, Each channel can be individually enabled.	155,00
XD-E8AD-V	14bit, 8 channel analog input module, 8 channels are voltage input, The first-order coefficient is adjustable , Each channel can be individually enabled.	155,00
XD-E3AD4PT2DA	4CH Pt100 temp sampling//0.1°C; 14bits 3CH analog input (0-20mA, 4-20mA selectable); 10bits 2CH analog output (0-5V, 0-10V selectable); the current output is pull current, source output	172,00
XD-E2AD2PT2DA	2CH PT100 temperature input (0.01°C resolution), with PID auto tune, separate PID parameters setting; 2CH 16bits analogue input (current, voltage selectable), 2CH 10 bits analogue output	225,00
XD-E6TC-P	0~1300°C, 6 channels thermocouple K temperature sensor use analog input ,resolution is 0.1 °C, 6 channel output PID parameters of 2groups(every 3 channel has one PID parameter).	155,00
XD-E6PT-P	-100~500°C, 6 channel pt100 temperature sampling module, resolution is 0.1°C, PID output.	155,00
XD-E2GRP	Tiny length measuring module	319,00
XD-E2WT-C	It can collect two channel analog voltage signal (0-10mV) of pressure sensor, 24 BIT high resolution A/D transition. use A/D transition mode of $\Delta-\Sigma$ ADC; DC 24V power supply	218,00
XD-E4WT-C	It can collect four channel analog voltage signal (0-10mV)of pressure sensor, 24 BIT high resolution A/D transition. Use A/D transition mode of $\Delta-\Sigma$ ADC. AC 230V power supply	345,00

XD-PLC Expansion Card		
XD-NS-BD	XD series BD, RS232 port	65,00
XD-NE-BD	XD series BD, BUS connection function, X-Net standard wiring interface, can be used as RS485 also	65,00
XD-NO-BD	XD series BD, BUS connection function, X-Net optical wiring interface, can be used as RS485 also	62,00
JD-P03	Program download device for XD/XL PLC (for program download without PC)	62,00
JM-TF-16	XD series BD card, support SD card, 16GB	60,00
XD-ETR	Terminal resistor for 5 or more expansion modules	8,00

XD-PLC ED Module (Left Expansion Module)		
XD-4AD-A-ED	Left expansion module, 4CH 12Bits analog current input	59,00
XD-4AD-V-ED	Left expansion module, 4CH 12Bits analog voltage input	59,00
XD-4DA-A-ED	Left expansion module, 4CH 12Bits analog current output	68,00
XD-4DA-V-ED	Left expansion module, 4CH 12Bits analog voltage output	68,00
XD-2AD2DA-A-ED	Left expansion module, 2CH 12bits current input, 2CH 10bits current output	65,00
XD-2AD2DA-V-ED	Left expansion module, 2CH 12bits voltage input, 2CH 10bits voltage output	65,00
XD-2AD2PT-A-ED	Left expansion module, 2CH 12bits current input, 2CH Pt100 temperature sampling	62,00
XD-2AD2PT-V-ED	Left expansion module, 2CH 12bits voltage input, 2CH Pt100 temperature sampling	62,00
XD-2PT2DA-A-ED	Left expansion module, 2CH Pt100 temperature sampling, 2CH 10bits current output	68,00
XD-2PT2DA-V-ED	Left expansion module, 2CH Pt100 temperature sampling, 2CH 10bits voltage output	68,00
XD-WBOX-ED	XD PLC left side expansion, WIFI expansion module	125,00
XD-SBOXT-ED	XD PLC left side expansion, S-BOX 433MHZ communication, occupy PLC port3	125,00
XD-NES-ED	XD PLC left side expansion, can expand RS232 or RS485 port	62,00

XL series PLC

1. XL3 series ultra- thin PLC

Model	Functions	Price (EUR)
XL3-16R	8 input/8 output, relay output, power supply DC24V, 3 AB phases count, it has faster processing speed than XC series PLC	91,00
XL3-16T	8 input/8 output, transistor output, power supply DC24V, 3 AB phases count, it has faster processing speed than XC series PLC	91,00
XL3-32T	16 input/16 output, transistor output, power supply DC24V, 3 AB phases count, it has faster processing speed than XC series PLC	168,00

2. XL5/E series ultra- thin PLC

Model	Functions	Price (EUR)
XL5-16T	8 input/8 output, transistor output, power supply DC24V, 3 AB phases counter, 2 puls output, more register than XL3	119,00
XL5-32T	16 input/16 output, transistor output, power supply DC24V, 3 AB phases counter, 2 puls output, more register than XL3	175,00
XL5-32T4	16 input/16 output, transistor output, power supply DC24V, 4 AB phases counter, 4 puls output, more register than XL3	200,00
XL5E-16T	8 input/8 output, transistor output, power supply DC24V, 3 AB phases counter, 2 puls output, more register than XL3, Ethernet port	123,00
XL5E-32T	16 input/16 output, transistor output, power supply DC24V, 3 AB phases counter, 2 puls output, more register than XL3, Ethernet port	206,00
XL5E-32T4	16 input/16 output, transistor output, power supply DC24V, 4 AB phases counter, 4 puls output, more register than XL3, Ethernet port	217,00

XL5E-64T6	32 input/32 output, transistor output, power supply DC24V, 6 AB phases counter, 6 puls output, more register than XL3, Ethernet port	292,00
XLME-32T4	16 input/16 output, transistor output, power supply DC24V, 4 AB phases counter, 4 puls output, more register than XL3, Ether200net port	280,00

3. XL series I/O expansion modules

XL-E16X	16 DC input	57,00
XL-E32X	32 DC input (JT I/O terminal block required)	108,00
XL-E8X8YR	8 DC input, 8 relay output (JT I/O terminal block required)	59,00
XL-E8X8YT	8 DC input, 8 transistor output (JT I/O terminal block required)	59,00
XL-E16X16YT-E	16 DC input, 16 transistor output (JT I/O terminal block required)	106,00
Digital Output Expansion:		
XL-E16YT	16 transistor output.	59,00
XL-E16YR	16 relay output.	59,00
XL-E16YT-A	16 transistor output.	59,00
XL-E32YT	extend 32 transistor output (JT I/O terminal block required)	117,00

4. XL-PLC analog expansion modules, power supply module and others

Model	Functions	Price (EUR)
XL-E4DA	12bit, 4 channel analog output module (0~10V 0~5V -10~10V -5~5V, 0~20mA, 4~20mA)	160,00

XL-E8AD-A	14bit,8 channel analog input module (0~20mA, 4~20mA, -20~20mA)	160,00
XL-E8AD-V	14bit,8 channel analog input module (0~10V 0~5V -10~10V -5~5V)	160,00
XL-P50-E	50W power supply module for XL PLCs, 230VAC input, 24V output	46,00
XL-ETR	Terminal resistor for 5 and more connected XL modules	17,00
XL-E4AD2DA	14bit, 4 channel analog input (current or voltage), 12bit, 2 channel analog output module(current or voltage),The first-stage coefficient is adjustable, Each channel can be individually enabled.	188,00
XL-E4TC-P	4 channel thermocouple input, resolution is 0.1 °C, individual PID parameter set for every input	149,00
XL-E4PT3-P	-100~500° C, 4 channel PT100 temperature sampling module, resolution is 0.1° C, PID output	169,00
JT-E32X	I/O terminal block for XL-E32X	48,00
JT-E16YT-A	I/O terminal block for XL-E16YT-A	48,00
JT-E16X16YT	I/O terminal block for XL-E16X16YT	48,00
JT-E32YT	I/O terminal block for XL-E32YT	48,00
JC-TE32-NN05	Extension cable for XL terminal block (0.5m)	31,00
JC-TE32-NN10	Extension cable for XL terminal block (1m)	32,00
JC-TE32-NN15	Extension cable for XL terminal block (1.5m)	37,00

5. XL-PLC ED Module (Left Expansion Module)

XL-4AD-A-ED	Left expansion module, 4CH 12Bits analog current input	62,00
XL-4AD-V-ED	Left expansion module, 4CH 12Bits analog voltage input	62,00
XL-4DA-A-ED	Left expansion module, 4CH 12Bits analog current output	74,00

XL-4DA-V-ED	Left expansion module, 4CH 12Bits analog voltage output	74,00
XL-2AD2DA-A-ED	Left expansion module, 2CH 12bits current input, 2CH 10bits current output	72,00
XL-2AD2DA-V-ED	Left expansion module, 2CH 12bits current input, 2CH 10bits voltage output	72,00
XL-2AD2PT-A-ED	Left expansion module, 2CH 12bits current input, 2CH Pt100 temperature sampling	72,00
XL-2AD2PT-V-ED	Left expansion module, 2CH 12bits voltage input, 2CH Pt100 temperature sampling	72,00
XL-2PT2DA-A-ED	Left expansion module, 2CH Pt100 temperature sampling, 2CH 10bits current output	72,00
XL-2PT2DA-V-ED	Left expansion module, 2CH Pt100 temperature sampling, 2CH 10bits voltage output	72,00
XL-NES-ED	XD PLC left side expansion, Can expand RS232 or RS485 port	55,00

Ethernet Module

Model	Function	Price (EUR)
T-BOX	Ethernet module, multi-master, multi-slave networking, remote monitor and download/upload PLC program	185,00
A-BOX-W	Network module, support for WIFI/RJ45 network connection, support RS232/485/422 serial connection, for remote monitoring, remote programming and Xinje Cloud. Can be used with PLCs, touch panels and micro controllers from other manufacturers.	182,00
XC-TBOX-BD	Ethernet BD card, realize TBOX module's functions	76,00
G-BOX	Wireless Ethernet module, support remote wireless monitor, program upload/download, cell phone SMS	115,00
W-Box	WIFI expansion module, suitable for XC and XD, occupy PLC RS232 port	125,00
S-Box-T	S-BOX 433MHZ module, suitable for XC and XD, occupy PLC RS232 port	125,00

Simple SCADA

USB Dongle	Real-time monitor the PLC's status, used for T-BOX、 G-BOX modules and related BD cards;	226,00
-------------------	---	---------------

HMI Human Machine Interface

1. OP series

Model	Function	Price (EUR)
OP320	3.7 inch monochrome LCD, 24V,192*64 pixels, 7 function keys, RS232/RS422	76,00
OP320-S	3.7 inch monochrome LCD, 24V,192*64 pixels, 7 function keys, RS232/RS485	76,00
OP320-A	3.7 inch monochrome LCD, 24V,192*64 pixels, 20 function keys, RS232/RS422	76,00
OP320-A-S	3.7 inch monochrome LCD, 24V,192*64 pixels, 20 function keys, RS232/RS485	76,00

2. TG series

Model	Function	Price (EUR)	
TG465-MT	1 PLC Port, Supports RS232/RS485/RS422	139,00	
TG465-UT	4.3 inch 16 million color, 480*272 resolution, CPU 400MHz frequency, 128M memory; Mounting dimension 144.0*94.0; USB-B downloading,	1 PLC port, Supports RS232/RS485/RS422, 1 USB-A port, supports CSV data import and export and USB-disk program downloading	155,00
TG465-UT2	4.3 inch 16 million color, 480*272 resolution, CPU 400MHz frequency, 128M memory; Mounting dimension 144.0*94.0; USB-B downloading,	2 COM ports , PLC port supports RS232/RS485/RS422, Download port supports RS232/RS485, 1 USB-A port , supports CSV data import and export and USB-disk program downloading 2 COM ports , PLC port supports RS232/RS485/RS422, Download port supports RS232/RS485, 1 USB-A port , supports CSV data import and export and USB-disk program downloading	172,00

TG465-ET		1 PLC port , Supports RS232/RS485/RS422, 1 USB-A port , supports CSV data import and export and USB-disk program downloading; 1 Ethernet port , supports Modbus TCP protocol	177,00
TG765-UT	7 inch 16 million color, 800*480 resolution, CPU 400MHz frequency, 128M memory; USB-B downloading; Mounting dimension 192.0*138.5; Support vertical installation	2 COM ports , PLC port supports RS232/RS485/RS422, Download port supports RS232/RS485; Supports X-Net bus (only one-panel mode, max baudrate is 115200), 1 USB-A port , supports CSV data import and export and USB-disk program downloading	225,00
TG765-ET	7 inch 16 million color, 800*480 resolution, CPU 400MHz frequency, 128M memory; USB-B downloading; Mounting dimension 192.0*138.5; Support vertical installation	2 COM ports , PLC port supports RS232/RS485/RS422, Download port supports RS232/RS485; Supports X-Net bus (only one-panel mode, max baudrate is 115200), 1 USB-A port , supports CSV data import and export and USB-disk program downloading; 1 Ethernet port , supports Modbus TCP protocol	245,00
TG865-ET	8 inch 16 million color, 800*600 resolution, CPU 400MHz frequency, 128M memory; Mounting dimension 211.4*157.8; USB-B downloading; Support vertical installation	2 COM ports , PLC port supports RS232/RS485/RS422, Download port supports RS232/RS485; Supports X-Net bus (only one-panel mode, max baudrate is 115200), 1 USB-A port , supports CSV data import and export and USB-disk program downloading; 1 Ethernet port , supports Modbus TCP protocol	426,00

	<p>211.4*157.8; downloading; Support vertical installation</p>	<p>2 COM ports, PLC port supports RS232/RS485/RS422, Download port supports RS232/RS485; Supports X-Net bus (only one-panel mode, max baudrate is 115200), 1 USB-A port, supports CSV data import and export and USB-disk program downloading; 1 Ethernet port, supports Modbus TCP protocol</p>	
<p>TGA62-UT</p>	<p>10.1 inch 16 million color, 800*480 resolution, CPU 400MHz frequency, 128M memory; Mounting dimension 260.2*179,7; USB-B</p>	<p>2 COM ports, PLC port supports RS232/RS485/RS422, Download port supports RS232/RS485; Supports X-Net bus (only one-panel mode, max baudrate is 115200), 1 USB-A port, supports CSV data import and export and USB-disk program downloading</p>	<p>332,00</p>
<p>TGA62-ET</p>	<p>downloading; Support vertical installation10.1 inch 16 million color, 800*480 resolution, CPU 400MHz frequency, 128M memory; Mounting dimension 260.2*179,7; USB-B downloading; Support vertical installation</p>	<p>2 COM ports, PLC port supports RS232/RS485/RS422, Download port supports RS232/RS485; Supports X-Net bus (only one-panel mode, max baudrate is 115200), 1 USB-A port, supports CSV data import and export and USB-disk program downloading; 1 Ethernet port, supports Modbus TCP protocol</p>	<p>352,00</p>

TGMA63S-ET	10.1" touch panel, 16 million TFT true color, 1024*600 pixels, 128M memory, support Ethernet	3 COM ports, PLC port supports RS232/RS485/RS422, Download port supports RS232/RS485; Supports X-Net bus (only one-panel mode, max baudrate is 115200), 1 USB-A port	352,00
TGC65-ET	15.6inch, 16 million color, 1366*768 resolution; memory size: 128M; USB-B downloading; mounting dimension: 399.0*259.0; Support vertical installation	2 COM ports , PLC port supports RS232/RS485/RS422, Download port supports RS232/RS485; Supports X-Net bus (only one-panel mode, max baudrate is 115200), 1 USB-A port , supports CSV data import and export and USB-disk program downloading; 1 Ethernet port , supports Modbus TCP protocol	900,00
TGM465-ET	4.3 inch 16 million color, 480*272 resolution, CPU 400MHz frequency, 128M memory; Mounting dimension 144.0*94.0; USB-B downloading,	1 PLC port, Supports RS232/RS485/RS422, 1 USB-A port, supports CSV data import and export and USB-disk program downloading; 1 Ethernet port, supports Modbus TCP protocol, support Ethernet, support remote program download.	185,00

TGM765S-ET	7 inch 16 million color, 800*480 resolution, CPU 400MHz frequency, 128M memory; USB-B downloading; Mounting dimension 192.0*138.5; Support vertical installation	2 COM ports, PLC port supports RS232/RS485/RS422, Download port supports RS232/RS485; Supports X-Net bus (only one-panel mode, max baudrate is 115200), 1 USB-A port, supports CSV data import and export and USB-disk program downloading; 1 Ethernet port, supports Modbus TCP protocol, support Ethernet, support remote program download.	275,00
TGMC65-ET	15.6inch, 16 million color, 1366*768 resolution; memory size: 128M; USB-B downloading; mounting dimension: 399.0*259.0; Support vertical installation	2 COM ports, PLC port supports RS232/RS485/RS422, Download port supports RS232/RS485; Supports X-Net bus (only one-panel mode, max baudrate is 115200), 1 USB-A port, supports CSV data import and export and USB-disk program downloading; 1 Ethernet port, supports Modbus TCP protocol, support Ethernet, support remote program download.	939,00
MTG765-UT	7 inch, 16 million color, 800x480 resolution; memory size: 128M; USB-B downloading;	hand held wireless touch panel with internal battery, wireless communication with PLC (S-BOX)	463,00

NOTE:

- 1.For X-net function, TG series panels only support the OMMS form, i.e. one-panel to one-device, one-panel to multi-devices
2. Only Panels at V2.D.3c and above support USB-Disk program download function
3. For panel TG465-MT/UT, V3.0 and above support RS232/RS485/RS422

3. Communication Cable

Model	Function	Price (EUR)
OP-PC-CAB	OP, TP downloading (PC-TP/OP)	5,00
TH-PC-USB	TH program downloading (PC-TH)	5,00
XVP-CAB	Cable link XC-PLC to PC, to TouchWin HMI	5,00
Converter	USB-RS232-CONV	19,00
Diff-OC	5V differential to open collector converter	39,00
OC-Diff	5V open collector to differential converter	39,00

XP series PLC+HMI Combination

Model	Function	Price (EUR)
ZG3-20R-4	TG465 panel combined with XD3-20 PLC (10DI/10DO, relay output, 2CH pulse output, 3CH AB-phase count, 8CH external interruption), can expand one BD card, mounting dimension: 144*94	255,00
ZG3-20T-4	TG465 panel combined with XD3-20 PLC (10DI/10DO, transistor output, 2CH pulse output, 3CH AB-phase count, 8CH external interruption), can expand one BD card, mounting dimension: 144*94	255,00
ZG3-30R-7	TG765 panel combined with XD3-30 PLC (16DI/14DO, relay output, 3CH AB-phase count, 10CH external interruption), can expand one BD card, mounting dimension: 192*138.5	317,00
ZG3-30T-7	TG765 panel combined with XD3-30 PLC (16DI/14DO, transistor output, 2CH pulse output, 3CH AB-phase count, 10CH external interruption), can expand one BD card, mounting dimension: 192*138.5	317,00
ZGM-30T4-7	TG765 panel combined with XDM PLC (16DI/14DO, transistor output, 4CH pulse output, 4CH AB-phase count, 10CH external interruption), can expand one BD card, mounting dimension: 192*138.6	335,00

Expansion

Model	Function	Price (EUR)	
Z-3AD3PT-BD	ZG3 series BD card, 3CH 0-10V/0-5V 12bit voltage input; 3CH Pt100 -100~+500 °C, 0.1°C resolution	60,00	ZG3 series
Z-4AD2DA-A-BD	ZG3 series BD card, 4CH 0-20mA/4-20mA 12bit current input; 2CH 0-20mA/4-20mA 10bit current output, sucker type, needs external power supply	60,00	

NOTE:

The current output of BD card needs to add external power supply, the load should be connected between AO and COM, $RL < 500\Omega$;

VFD

1. VH5/VH6 series

Model		
VH5-40P7-B	Suitable motor:0.75KW; rated output current: 2.1A;External dimension: 94*188*138mm	237,00
VH5-41P5-B	Suitable motor: 1.5KW; rated output current: 3.8A;External dimension: 94*188*138mm	272,00
VH6-43P7-B	Full function inverter with closed loop vector control via resolver feedback. EtherCAT, CANopen support with expansion card. Suitable motor: 3,7KW; rated output current: 9A;External Dimension: 110*305*202mm	260,00
VH6-45P5-B	Full function inverter with closed loop vector control via resolver feedback. EtherCAT, CANopen support with expansion card. Suitable motor: 5.5KW; rated output current: 13A;External Dimension: 110*305*202mm	291,00

2. VH5/VH6 series VFD expansion modules

VH5-CN100	CANopen communication expansion card ; supports three indicator lights, dual network ports; access in the wiring mode; this expansion card does not come standard when it leaves the factory, users can purchase this expansion card when the inverter needs to network the CANopen network	54,00
VH5-CC100	EtherCAT communication expansion card ; supports three indicator lights, dual network ports; access in the wiring mode; this expansion card does not come standard	57,00
VH6-CN100	CANopen communication expansion card ; supports three indicator lights, dual network ports; access in the wiring mode; this expansion card does not come standard when it leaves the factory, users can purchase this expansion card when the inverter needs to network the CANopen network	54,00
VH6-CC100	EtherCAT communication expansion card ; supports three indicator lights, dual network ports; access in the wiring mode; this expansion card does not come standard	57,00

SERVO SYSTEMS - SERVO DRIVER/SERVO MOTOR

1. DS5C-PTA **ETHERCAT** BUS TYPE SERIES

Motor	power (KW)	Voltage (V)	RPM	Torque (N.m)	Driver	Price (EUR/Set)
MS6S-60CM30B1-20P4 low inertia	0,4	220VAC±10%	3000	1,27	DS5C-20P4-PTA	510,00
MS6H-60CM30B1-20P4 high inertia	0.4		3000	1.27	DS5C-20P4-PTA	525,00
MS6S-80CM30B1-20P7 low inertia	0.75		3000	2.39	DS5C-20P7-PTA	553,00
MS6H-80CM30B1-20P7 high inertia	0.75		3000	2.39	DS5C-20P7-PTA	569,00
MS6S-80CM20B1-20P7 low inertia	0.75		2000	3.50	DS5C-20P7-PTA	599,00
MS6H-80CM20B1-20P7 high inertia	0.75		2000	3.50	DS5C-20P7-PTA	615,00
MS6H-130CM20B2-21P5 high inertia	1.5		2000	7.16	DS5C-21P5-PTA	907,00
MS6S-100CM30B2-21P5 low inertia	1.5		3000	4.78	DS5C-21P5-PTA	821,00

2. DS5C1-PTA **ETHERCAT** BUS TYPE SERIES, **without pulse control**

Motor	power (KW)	Voltage (V)	RPM	Torque (N.m)	Driver	Price (EUR/Set)
MS6H-60CM30B1-20P4 high inertia	0.4		3000	1.27	DS5C1-20P4-PTA	503,00
MS6H-80CM30B1-20P7 high inertia	0.75		3000	2.39	DS5C1-20P7-PTA	539,00
MS6H-80CM30B3-21P0 high inertia	1		3000	3.18	DS5C1-21P0-PTA	745,00
MS6H-130CM20B2-21P5 high inertia	1.5		2000	7.16	DS5C1-21P5-PTA	893,00

3. DS5L1-PTA **without ETHERCAT** PULSE TYPE SERIES

Motor	power (KW)	Voltage (V)	RPM	Torque (N.m)	Driver	Price (EUR/Set)
MS6H-60CM30B1-20P4 high inertia	0.4		3000	1.27	DS5L1-20P4-PTA	480,00

4. DS5 Servo Cable

Driver Model	Encoder cable	Motor cable	Length (m)	Price (EUR)
DS5L/C/F/K-20P1/2/4/7-PTA	CP-SP-BM-03	CM-P07-M-03	3	32,00
DS5L/C/F/K-20P1/2/4/7-PTA	CP-SP-BM-05	CM-P07-M-05	5	37,00
DS5E/L/C/F/K-21P0/21P5/22P3/22P6-PTA	CP-SC-B-03	CM-L15-03	3	61,00
DS5E/L/C/F/K-21P0/21P5/22P3/22P6-PTA	CP-SC-B-05	CM-L15-05	5	66,00
DS5L1/C1-20P1/2/4/7-PTA	CP-SP-BM-03	CM-P07A-M-03	3	32,00
DS5C/E/K/F/L1/C1/N1-20P2/4/7/21P0-PTA	CP-SE-BM-03	CM-E05A-03	3	37,00
DS5L1/C1-20P7/21P0/21P5/22P3/22P6-PTA, DS5C1/L1-41P0/41P5/42P3-PTA	CP-SC-B-03	CM-L15B-03	3	56,00

All prices are in EURO without VAT!

PL Control Ltd reserves the right to change the prices if necessary!

We are pleased to discuss the possibility of supplying the equipment you need with the parameters suitable for your project!

PL Control Ltd